

## T-606H



6.5" High-end Entertainment Conference Loudspeaker, 120W@8Ω



## **Description:**

It works with the professional amplifiers and audio processors, forming a set of high-end professional sound system with perfect sound effects and outstanding vocal performance. It is applicable to karaoke rooms, high-end conference rooms, multi-function halls and other places.

## Feature:

- \* Adopt 1 mid-woofer and 2 cone tweeters.
  \* 12mm plywood housing, light weight, wear-resistant spray paint treatment, and dust-proof net cotton outside.
- \* The frequency divider in precise design optimizes the vocal MF performance.

## **Specification:**

$\begin{array}{llllllllllllllllllllllllllllllllllll$	•	
Frequency response         70Hz-20KHz           Rated power         120W           Peak power         480W           Sensitivity         95dB/W/M           Max SPL(rated/peak)         117dB/122dB           Coverage angle         (H)120° (V)60°           Tweeter         3" cone tweeter ×2           Woofer         6.5" woofer ×1           Size         215×310×208mm(H×W×D)	Model	TS-606H
Rated power         120W           Peak power         480W           Sensitivity         95dB/W/M           Max SPL(rated/peak)         117dB/122dB           Coverage angle         (H)120° (V)60°           Tweeter         3" cone tweeter ×2           Woofer         6.5" woofer ×1           Size         215×310×208mm(H×W×D)	Impedance	8Ω
Peak power         480W           Sensitivity         95dB/W/M           Max SPL(rated/peak)         117dB/122dB           Coverage angle         (H)120° (V)60°           Tweeter         3" cone tweeter ×2           Woofer         6.5" woofer ×1           Size         215×310×208mm(H×W×D)	Frequency response	70Hz-20KHz
Sensitivity         95dB/W/M           Max SPL(rated/peak)         117dB/122dB           Coverage angle         (H)120° (V)60°           Tweeter         3" cone tweeter ×2           Woofer         6.5" woofer ×1           Size         215×310×208mm(H×W×D)	Rated power	120W
Max SPL(rated/peak)         117dB/122dB           Coverage angle         (H)120° (V)60°           Tweeter         3" cone tweeter ×2           Woofer         6.5" woofer ×1           Size         215×310×208mm(H×W×D)	Peak power	480W
Coverage angle         (H)120° (V)60°           Tweeter         3" cone tweeter ×2           Woofer         6.5" woofer ×1           Size         215×310×208mm(H×W×D)	Sensitivity	95dB/W/M
Tweeter         3" cone tweeter ×2           Woofer         6.5" woofer ×1           Size         215×310×208mm(H×W×D)	Max SPL(rated/peak)	117dB/122dB
Woofer         6.5" woofer ×1           Size         215×310×208mm(H×W×D)	Coverage angle	(H)120° (V)60°
<b>Size</b> 215×310×208mm(H×W×D)	Tweeter	3" cone tweeter ×2
· · · ·	Woofer	6.5" woofer ×1
Weight 5.7Kg	Size	215×310×208mm(H×W×D)
	Weight	5.7Kg